## **Electric Scissor Lift PLHP 10 HXE**

## **Electric Scissor Lift**

- Adjustable working platform with lifting of weights to a height of 800 mm, suitable for workshops.
- Great reliability and practicality thanks to innovative frontal protection and reduced weight.
- Emergency stop, which also disconnects the battery.
- Battery and external charger included.





P	LHP 10	HXE - General specifications				
Characteristics	1.1	Manufacturer		Yale		
	1.2	Model designation		PLHP 10 HXE		
	1.3	Power: battery, diesel, LPG, electric mains		Manual		
	1.4	Operation: manual, pedestrian, stand, seat, order picker		Pedestrian		
	1.5	Load capacity	Q (kg)	1000		
	1.6	Load centre distance	c (mm)	600		
	1.8	Load distance, centre of drive axle to fork	x (mm)	993		
	1.9	Wheel base	y (mm)	1231		
Weight	2.1	Service weight with battery (see line 6.5)	(kg)	141		
	2.2	Axle load laden, front / rear	(kg)	381		760
	2.3	Axle load unladen, front / rear	(kg)	113		28
Wheels & Tyres	3.1	Tyres: rubber, polyurethane, vulkolan front / rear		Rubber		
	3.2	Tyre size, front		Ø 80 x 50		
	3.3	Tyre size, rear		Ø 200 x 45		
	3.5	Wheels, number front / rear		2/2		
	3.6	Tread, front	b <sub>10</sub> (mm)	151		
	3.7	Tread, rear	b <sub>11</sub> (mm)	447		
Dimensions	4.4	Lift height	h <sub>3</sub> (mm)	715		
	4.9	Height of tiller arm in working position min / max	h <sub>14</sub> (mm)	1300		
	4.15	Height, lowered	h <sub>13</sub> (mm)	85		
	4.19	Overall length	I <sub>1</sub> (mm)	1685		
	4.20	Length to face of forks	I <sub>2</sub> (mm)	540		
	4.21	Overall width	b <sub>1</sub> (mm)	540		
	4.22	Fork dimensions	s/e/l (mm)	48	160	1150
	4.25	Distance between fork arms	b <sub>5</sub> (mm)	540		
	4.32	Ground clearance, centre of wheelbase	m <sub>2</sub> (mm)	21		
	4.33	Aisle width with pallets 1000 x 1200 mm wide	Ast (mm)	1652		
	4.34	Aisle width with pallets 800 x 1200 mm wide	Ast (mm)	1852		
	4.35	Turning radius	Wa (mm)	1445		
Perf., el. motor	5.2	Lift speed, laden / unladen	(m/s)	0.08 0.13		0.13
	5.3	Lowering speed, laden / unladen	(m/s)	0.13 0.06		0.06
	6.2	Lift motor power	(kW)	1.6		
	6.4	Battery voltage, nominal capacity C5	(V/Ah)	12/60		
ف	6.5	Battery weight	(kg)	16		

