

Stainless steel Hand Pallet Truck

PLHP 20 I

Stainless steel Hand Pallet Truck

- The truck features 100% stainless steel pump, handle, frame and components construction.
- Nylon steering wheel and fork rollers as standard for maximum corrosion resistance in chemical, wet or cold applications.
- Providing durability, dependability and low maintenance, this unit is perfectly suited for chemical manufacturers, pharmaceutical companies, food manufacturers and fisheries.
- With pressure relief & overload valves to prevent pump damages when load exceeds weight limit.



PLHP 20 I - General specifications

Characteristics	1.1	Manufacturer		Yale	
	1.2	Model designation		PLHP 20 I	
	1.3	Power: battery, diesel, LPG, electric mains		Manual	
	1.4	Operation: manual, pedestrian, stand, seat, order picker		Manual / Tiller	
	1.5	Load capacity	Q (kg)	2000	
	1.6	Load centre	c (mm)	600	
	1.8	Load distance	x (mm)	985	
	1.9	Wheelbase	y (mm)	1215	
	2.1	Unladen weight	kg	82	
Wheels & Tyres	3.1	Tyres: rubber, polyurethane, vulkolan front / rear		Nylon	
	3.2	Tyre size, front		Ø 200 x 50	
	3.3	Tyre size, rear		Ø 80 x 93	Ø 80 x 70
	3.5	Wheels, number front / rear		2/2	2/4
	3.6	Track width, front	b_{10} (mm)	180	
	3.7	Track width, rear	b_{11} (mm)	440	430
Dimensions	4.4	Lift height	h_3 (mm)	200	
	4.9	Height of tiller arm in working position	h_{14} (mm)	1225	
	4.15	Height, lowered	h_{13} (mm)	85	
	4.19	Overall length	l_1 (mm)	1560	
	4.20	Length to face of forks	l_2 (mm)	410	
	4.21	Overall width	b_1/b_2 (mm)	520	685
	4.22	Fork dimensions	s/e/l (mm)	60	160
	4.25	Outside fork width	b_5 (mm)	520	685
	4.32	Ground clearance, centre of wheelbase	m_2 (mm)	30	
	4.33	Aisle width with pallets 1000 x 1200 mm wide	Ast (mm)	1548	
	4.34	Aisle width with pallets 800 x 1200 mm wide	Ast (mm)	1748	
	4.35	Turning radius	Wa (mm)	210	

Truck dimensions

