

Stainless steel Hand Pallet Truck

PLHP 20 I

Stainless steel Hand Pallet Truck

- The truck features 100% stainless steel pump, handle, frame and components construction.
- Nylon steering wheel and fork rollers as standard for maximum corrosion resistance in chemical, wet or cold applications.
- Providing durability, dependability and low maintenance, this unit is perfectly suited for chemical manufacturers, pharmaceutical companies, food manufacturers and fisheries.
- With pressure relief & overload valves to prevent pump damages when load exceeds weight limit.



PLHP 20 I - General specifications

Characteristics	1.1	Manufacturer	Yale			
	1.2	Model designation	PLHP 20 I			
	1.3	Power: battery, diesel, LPG, electric mains	Manual			
	1.4	Operation: manual, pedestrian, stand, seat, order picker	Manual / Tiller			
	1.5	Load capacity	Q (kg)	2000		
	1.6	Load centre	c (mm)	600		
	1.8	Load distance	x (mm)	985		
	1.9	Wheelbase	y (mm)	1215		
	2.1	Unladen weight	kg	82		
Wheels & Tyres	3.1	Tyres: rubber, polyurethane, vulkolan front / rear	Nylon			
	3.2	Tyre size, front	Ø 200 x 50			
	3.3	Tyre size, rear	Ø 80 x 93	Ø 80 x 70		
	3.5	Wheels, number front / rear	2/2	2/4		
	3.6	Track width, front	b_{10} (mm)	180		
	3.7	Track width, rear	b_{11} (mm)	440	430	
	Dimensions	4.4	Lift height	h_3 (mm)	200	
4.9		Height of tiller arm in working position	h_{14} (mm)	1225		
4.15		Height, lowered	h_{13} (mm)	85		
4.19		Overall length	l_1 (mm)	1560		
4.20		Length to face of forks	l_2 (mm)	410		
4.21		Overall width	b_1/b_2 (mm)	520	685	
4.22		Fork dimensions	s/e/l (mm)	60	160	1150
4.25		Outside fork width	b_5 (mm)	520	685	
4.32		Ground clearance, centre of wheelbase	m_2 (mm)	30		
4.33		Aisle width with pallets 1000 x 1200 mm wide	Ast (mm)	1548		
4.34		Aisle width with pallets 800 x 1200 mm wide	Ast (mm)	1748		
4.35		Turning radius	Wa (mm)	210		

Truck dimensions

